

METERS



SUZZARA BLUE K24




Accuracy +/- **1%**
Possibility of calibration.
Flow rate up to **30** gpm

EN Meter easy to install, in line or at the end of the delivery hose, it is provided with a compact easy readable display. It is possible to apply the meter directly on the nozzle. User can quickly substitute the 2 batteries. Display can be rotated in 4 different positions.

Impulse type signals:
single channel, reed switch.
Electronic card with LCD display:
5 digit partial total from 0.1 to 99999, 6 digit total from 1 to 999999.
Resettable total available.
Flow rate indication.


ES Este cuentakilros es de facil instalación, en línea o en el extremo de la manguera de suministro, y está dotado de un display compacto de fácil lectura. El cuentakilros puede aplicarse directamente en la pistola. Dos baterías fáciles de sustituir alimentan el cuentakilros. La pantalla puede ser girada en cualquier posición.

Tipo de señal por impulso: mono-canal, interruptor de láminas.
Tarjeta electrónica con display LCD: Parcial de 5 cifras de 0.1 a 99999, Total de 6 cifras de 1 a 999999.
Total borrable disponible.
Indicación del caudal.



K24 Pulse-meter
Flow rate up to **30** gpm
Accuracy ± **1** %
Pulse out **23** ppg
(max distance 49 ft)

Socket 1" BSP/BSP




SUZZARA BLUE TURBINOX

Accuracy +/- **1%**
Possibility of calibration.
Flow rate up to **10** gpm
Puls OUT **26** p/gpm

EN This meter is easy to install. A tight stainless steel body provides endurance for use in every conditions. Also available a pulser display to connect an external receiver. User can quickly substitute the 2 display batteries.

ES Este cuentakilros se instala fácilmente. Su robusto cuerpo de acero inoxidable lo hace resistente y apto para ser utilizado prácticamente en cualquier condición. Es disponible también un display emisor de impulsos para conexión a receptor externo. (El display es alimentado por dos baterías de fácil sustitución).



Inline pulse meter

Remote display with Pulse OUT



Code	Description	Flow rate gpm	Pressure psi	Display	Pulse OUT (p/g)		Weight Lb	Packaging Inch
					Pulser version	Display version		
F00407340	K24 Meter (1 socket) GAL	1,3 - 30	300	Yes			1,1	Blister
F0040721B	K24 Pulse-meter (1 socket)	1,3 - 30	300	No	23	23	1,1	Blister
F0042000A	Inline turbine pulse meter	1,6 ÷ 10	420	No	23		1,6	9x4,7x6
F0049503B	Remote display with Pulse OUT			Yes		1 ÷ 100	2,2	9x4,7x6
F16073000	Socket 1" BSP/BSP (20 pcs)						5,3	Box (20 pcs)

SUZZARA NOZZLE WITH BLUE K24

EN The simple solution to directly control your DEF dispensing. The K24 meter is installed inline on the nozzle.

ES Una simple solució que permite de vigilar directamente tu suministro de DEF. El cuentakilros K24 es instalado sobre la pistola.



Automatic nozzle with K24



Manual nozzle with K24

Flow rate up to **11** gpm
Spout ext. Ø **3/4"**
Hose tail **3/4** with swivel

Flow rate up to **20** gpm
Spout ext. Ø **3/4"**
Hose tail **3/4** with swivel

Code	Description	Flow rate gpm	Pressure psi	Connections		Display	Weight Lb	Packaging Inch
				Inlet	Outlet			
F00870000	Automatic nozzle with K24	2 ÷ 18	50	3/4"	3/4"	Yes	6,6	16x11x4
F00870020	Manual nozzle with K24	2 ÷ 30	50	3/4"	3/4"	Yes	1,6	16x11x4

Adapter K24 for automatic nozzle M 3/4" BSP - F 1" BSP

Code **F16475000**



Plastic adapter for K24 manual nozzle

Code **F15776000**

